ADOPTED

AUG 13 1996

ORDINANCE NO. 116A-29

BOARD OF SUPERVISORS
JAMES CITY COUNTY
VIRGINIA

AN ORDINANCE TO AMEND AND REORDAIN CHAPTER 8, HEALTH AND SANITATION, OF THE

CODE OF THE COUNTY OF JAMES CITY, VIRGINIA, BY ADDING ARTICLE V, CROSS-

CONNECTION CONTROL AND BACKFLOW PREVENTION; SECTION 8-41, SHORT TITLE; SECTION

8-42, PURPOSE OF ARTICLE; SECTION 8-43, AUTHORITY FOR ARTICLE; SECTION 8-44,

VIOLATIONS OF ARTICLE; SECTION 8-45, DEFINITIONS; AND SECTION 8-46, INSPECTION

REQUIREMENTS.

BE IT ORDAINED by the Board of Supervisors of the County of James City, Virginia, that Chapter 8, Health

and Sanitation, is hereby amended and reordained by adding Section 8-41, Short title; Section 8-42, Purpose of

article; Section 8-43, Authority for article; Section 8-44, Violations of article; Section 8-45, Definitions; and

Section 8-46, Inspection requirements.

Chapter 8. Health and Sanitation

Article V. Cross-Connection Control and Backflow Prevention

Sec. 8-41. Short title.

This Article shall be known and may be cited as the Cross-Connection and Backflow Prevention ordinance.

Sec. 8-42. Purpose of article.

The purposes of this article are to:

Ordinance to Amend and Reordain Chapter 8. Health and Sanitation

Page 2

(a) Protect the public water of James City County from the possibility of contamination, by isolating,

within its customers' private water systems, contaminants, or pollutants which could, under adverse

conditions, backflow through uncontrolled cross connections into the public water system;

(b) Eliminate or control existing cross connections, actual or potential, at each water outlet from the

consumer's waterline;

(c) Provide a continuing inspection program of cross-connection control which will systematically and

effectively control all actual or potential cross connections in the future.

Sec. 8-43. Authority for article.

This article provides for establishment and enforcement of a program of cross-connection control and

backflow prevention in accordance with Part II, Article 3, Cross Connection Control and Backflow Prevention

in Waterworks of the Commonwealth of Virginia, State Board of Health, Waterworks Regulations 1993, as

amended.

Sec. 8-44. Violations of article.

Any water supply system owner found to be in violation of any provision of this ordinance shall be served

a written notice of violation sent certified mail to the water supply system owner's last known address, stating

the nature of the violation, corrective action required and providing a reasonable time limit, not to exceed

30 days, from the date of receipt of the notice of violation, to bring the water supply system into compliance

with this article. Any owner of properties served by a connection to the waterworks found guilty of violating

any of the provisions of this article, or any written order of the general manager in pursuance thereof, may

Page 3

be charged with a Class 1 misdemeanor and upon conviction thereof shall be punished by a fine of not less

than \$500 or more than \$1,000 for each violation. Each day upon which a violation of the provisions of this

article shall occur shall be deemed a separate and additional violation for the purposes of this ordinance.

Sec. 8-45. Definitions.

For the purposes of this article, the following words and phrases shall have the meanings respectively

ascribed to them as follows:

Backflow prevention device - Any device, method, or type of construction, approved by the general manager

of the James City Service Authority, intended to prevent backflow into the waterworks.

Consumer's water system - Any water system located on the consumer's premises, supplied by, or in any

manner connected to, the waterworks.

Cross connection - Any connection or structural arrangement, direct or indirect, to the waterworks whereby

backflow can occur.

Degree of hazard - The level of health hazard, as derived from an evaluation of the potential risk to health

and the adverse effect upon the waterworks. The degrees are high, moderate, and low.

Premises - A piece of real estate; house or building and its land.

Ordinance to Amend and Reordain

Chapter 8. Health and Sanitation

Page 4

Service connection - The point of delivery of water to a customer's building service line as follows:

(a) If a meter is installed, the service connection is the downstream side of the meter;

(b) If a meter is not installed, the service connection is the point of connection to the waterworks.

(c) When the water purveyor is also the building owner, the service connection is the entry point

to the building.

Water supply - The waters that shall have been taken into the waterworks from all wells, streams, springs,

lakes, and other bodies of surface water (natural or impounded), and the tributaries thereto, and all

impounded groundwater, but the term "water supply" shall not include any waters above the point of intake

of such waterworks.

Water supply system - The water service pipes, water distributing pipes, and necessary connecting pipes,

fittings, valves, and all appurtenances beyond the waterwork's service connection.

Waterworks - A system that serves piped water for drinking or domestic use to:

(1) the public,

(2) at least 15 connections, or

(3) an average of 25 individuals for at least 60 days out of the year.

Ordinance to Amend and Reordain Chapter 8. Health and Sanitation

Page 5

The term 'waterworks" shall include all structures, equipment, and appurtenances used in the storage,

collection, purification, treatment, and distribution of pure water except the piping and fixtures inside the

building where such water is delivered.

Section 8-46. Inspection requirements.

Testing and inspection schedules shall be established by the general manager as outlined in the Program

for all backflow prevention devices. The interval between testing and inspections and overhauls of each

device shall be established in accordance with the type and condition of the device and the device

manufacturer's recommendations. Inspection and testing intervals shall not exceed one year unless otherwise

established by the general manager based on the degree of hazard, and overhaul intervals shall not exceed

five years unless otherwise noted in the program. Repairs and overhauls shall use the device manufacturer's

parts kit.

David L. Sisk, Chairman Board of Supervisors

Jano Blianner

Sanford B. Wanner Clerk to the Board

SUPERVISOR	VOTE
m 1 3 1 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	A 3770
TAYLOR	AYE
MAGOON	AYE
DEPUE	AYE
EDWARDS	AYE
STSK	AYE

Adopted by the Board of Supervisors of James City County, Virginia, this 13th day of August, 1996.

C8He&San.ord